

22857.

XP-002251368

AN - 1968-23680Q [25]

A - [001] 01- 143 144 155 163 166 169 170 171 30& 371 376 398 409 415 437  
481 485

- [002] 01- 140 371 376 473 551 560 561 623 629 720 723

CPY - KURS

DC - A00

FS - CPI

MC - A11-B15 A12-H

PA - (KURS ) KURASHIKI RAYON CO

PN - JP44000892B B 00000000 DW196800 000pp

PR - JP19670023081 19670410

- AB - J69000892 Abnormally shaped spinneret orifices which give rise to abnormal fibre are removed from service without cessation of spinning by blocking them with a rod of an absorbent or absorbent filler containing a monomer or prepolymer of a thermally and chemically stable thermosetting polymer.
- The mixed blocking compound has a Morse hardness after solidification which is less than that of the spinneret material.
  - It is composed of charcoal, graphite, chalk, talc, alabaster, etc.
  - Retained in spinneret until spinning finished when the plugs are easily washed out.

IW - BLOCK ABNORMAL SPIN ORIFICE ABNORMAL

IKW - BLOCK ABNORMAL SPIN ORIFICE ABNORMAL

NC - 001

OPD - 1967-04-10

ORD - 1900-00-00

PAW - (KURS ) KURASHIKI RAYON CO

TI - Blocking abnormal spinning orifices to prevent abnormal